



TST50U

FERRI[®]
SIMPLY.THE MOWER



UnimogPartner

Product information:

The TST50U model specially developed for UNIMOG can be installed directly on the front mounting plate of the device carrier. The front PTO is used for operation. Really versatile, the boom mower allows lateral boom widths up to 4.8 meters. The device works on both sides, the right and the left side ensuring maximum visibility. For the operations a roll stabilization (delivery Ferri) is absolutely recommended.

Product advantages

a) ideal for spring and summer side road maintenance; b) strong and flexible for hard working conditions; c) All-Safety-Only-One-Operator product

Basic information

Model variants

40509012

Vehicle model

U218

Wheelbase

2.800 mm

Body mounting duration

1 Tag

Unladen body weight

1140kg

Euro standard

M5M: Engine version Euro VI,
with OBD-C

Minimum vehicle specification

CP3: Implement mounting plate DIN76060 type B, cat. 3

CA4: Rear mounting brackets

HN2: Single-circuit hydraul. sys., 2-cell, fully prop.

E45: Front plug-in socket 24V, 7 poles

N08: Live PTO incl. PTO front

DH3: Holder, universal, for control panel



transport position



TST50U with TN100 at work



TST50U mit TN100 at work



SIMPLY.THE MOWER

Contact persons.

Ferri Srl
Mr. Stefano Rosato
Govoni 30
IT-44030 Tamara

Telephone 1: +39 3357235450

Email: s.rosato@ferrisrl.it

Website: <http://www.ferrisrl.it/home>

Ferri Srl is UnimogPartner. The status was issued following a positive appraisal of the company based on the criteria of quality, service, engineering and sales/marketing.

Information relating to the body is provided solely by the bodybuilder, and is placed on the site by the bodybuilder. Daimler Truck AG has not verified the information provided by the bodybuilder for correctness or completeness, and neither accepts any liability nor provides any form of warranty for this information.